







_Characteristics



ELECTRONIC AUTO-LEVEL

Through an electronic level probe the boiler is automatically filled and maintained to the right filling level.



AUTOMATIC CLEANING CYCLE Process for coffee



EASY SERVICE Fast access to the internal parts for quick and easy



ACTIVATED ELECTRONIC PRE-INFUSION

Management of the delayed activation of water solenoid in the first phase



DOUBLE READING GAUGE

Allows to control at the same time the boiler pressure and the distribution pressure.



groups cleaning.

LED LIGHTING OF THE WORK AREA Allows efficient working in any condition of environmental lighting.




SHOT TIMER


To accurately and reliably time coffee extraction.


All content is subject to illustrative purpose. The manufacturer reserves the right to modify without prior notice the technical characteristics, contents, and images indicated above. Last update 2023-5-14



Versions







28.35 inches / 720 mm

37.40 inches / 950 mm

3 group 18,860 SAR 2 steam taps 1 water tap

1 one-cup portafilters 3 two-cup portafilters



_Technical data		2 group	3 group
voltage	V	220-240	220-240
power imput	kW	3.3	6
steam boiler capacity	lt	10	14
steam boiler power	kW	2.95	5.6
pump power	kW	0.13	0.13
net weight	kg	55	69





REACH US

Mobile number: +966 53 885 9093

Website: www.rfa-sa.com , https://sanremosaudiarabia.com/

Online shop: https://shop.rfa-sa.com/ Email: customer-service@rfa-sa.com

Location: Al Thumama, Riyadh, Saudi Arabia











